DOI: <https://doi.org/10.15407/technd2018.06 . 054>

RATIONALIZATION OF DIMENSIONS FOR RING-SHAPED ROTOR OF WIND-ELECTRIC SWITCHED RELUCTANCE GENERATOR

Journal	Tekhnichna elektrodynamika
Publisher	Institute of Electrodynamics National Academy of Science of Ukraine
ISSN	1607-7970 (print), 2218-1903 (online)
Issue	No 6, 2018 (November/December)
Pages	54 – 57

Authors

V.V. Kozirsky^{1*}, O.D. Podoltsev^{2}, M.I. Tregub³**

¹ – National University of Life and Environmental Sciences of Ukraine,
Heroyiv Oborony st., 15, Kyiv, 03041, Ukraine,
e-mail: epafort1@ukr.net

² – Institute of Electrodynamics National Academy of Sciences of Ukraine,
pr. Peremohy, 56, Kyiv, 03057, Ukraine,
e-mail: podol@ied.org.ua

³ – Bila Tserkva National Agrarian University,
pl. 8/1 Soborna, Bila Tserkva, 09117, Ukraine,
e-mail: tregyb.m.i@gmail.com

* ORCID ID : <http://orcid.org/0000-0001-6780-9750>

** ORCID ID : <http://orcid.org/0000-0002-9029-9397>

Abstract

The effect of geometric dimensions of the ferromagnetic elements of ring-shaped rotor of the

switched reluctance generator on the multiplicity of the variation of magnetic circuit conductivity caused by rotor motion is studied by numerical simulation using finite-element method and experimental prototype. The quantitative relations of dimensions of the elements with square cross-section are determined to provide the maximum change in magnetic system conductivity at rotor motion and to improve the electromagnetic characteristics of the generator. References 7, figures 5.

Key words: switched reluctance generator, ring-shaped rotor, magnetic conductivity, rational geometric parameters, electromagnetic system.

Received: 05.03.2018

Accepted: 09.07.2018

Published: 23.10.2018

References

1. Sinchuk O.N., Kozakevich I.A., Yurchenko N.N. Sensorless control of switched reluctance motors of traction electromechanical systems. *Tekhnichna Elektrodynamika*. 2017. No 5. Pp. 62–66. (Ukr) DOI: <https://doi.org/10.15407/techned2017.05.062>
2. Alper N.J., Terzjn A.A. Induction generators. Moskva: Energiia, 1970. 192 p. (Rus)
3. Kozirsky V.V., Tregub M.I. Determine methodology of the type and geometric parameters of ring-shaped rotor wind turbine. *Problemy ta perspektyvy rozvytku enerhetyky, elektrotekhnolohii ta avtomatyky v APK*. Kyiv, 5–6 November, 2013. Pp. 57-58. (Ukr)
4. Kozirsky V.V., Tregub M.I. Axial induction generator. Patent UA 101118, 2012.
5. Darie E., Cepisca C., Darie I. The use of switched reluctance generator in wind energy applications. *Proc. of EPE-PEMC*, September 1 – 3, 2008, Poland. Pp. 1963-1966. DOI: <http://doi.org/10.1109/EPEPEMC.2008.4794441>

[ps://doi.org/10.5772/7358](https://doi.org/10.5772/7358)

6. Liu X., Chen Z. A Novel Excitation Assistance Switched Reluctance Wind Power Generator. *IEEE Transaction on Magnetics*. 2014. No 11. Vol. 50. Pp. 150-155. DOI: <https://doi.org/10.1109/TMAG.2014.2327798>

7. Nassereddine M., Rizk J., Nagrial N. Switched reluctance generator for wind power applications. *Proc. World Academy of Science, Engineering and Technology*. 2008. Vol. 31. Pp. 126-130.

[PDF](#)