

DOI: <https://doi.org/10.15407/techned2020.02.017>**SIMULATION OF THE ELECTRIC FIELD IN THE ELECTRODE SYSTEM TO CREATE OF A PULSED BARRIER DISCHARGE IN ATMOSPHERIC AIR IN THE PRESENCE OF WATER IN A DROPLET-FILM STATE**

Journal	Tekhnichna elektrodynamika
Publisher	Institute of Electrodynamics National Academy of Science of Ukraine
ISSN	1607-7970 (print), 2218-1903 (online)
Issue	No 2, 2020 (March/April)
Pages	17 - 22

Authors**V.O. Bereka^{1*}, I.V. Bozhko^{1**}, V.A. Brzhezitsky^{2***}, Ya. Haran^{2****}, Ye. A. Trotzenko^{2*****}**¹-Institute of Electrodynamics National Academy of Science of Ukraine,

Pr. Peremohy, 56, Kyiv, 03057, Ukraine,

e-mail: ws77@ukr.net

²-National Technical University of Ukraine "Igor Sikorsky Kyiv Polytechnic Institute",

Pr. Peremohy, 37, Kyiv, 03056, Ukraine,

* ORCID ID : <https://orcid.org/0000-0003-0888-2864>** ORCID ID : <https://orcid.org/0000-0002-7955-246X>*** ORCID ID : <https://orcid.org/0000-0002-9768-7544>**** ORCID ID : <https://orcid.org/0000-0003-3242-9218>***** ORCID ID : <https://orcid.org/0000-0001-9379-0061>**Abstract**

By simulation, it was stated the distribution of the electric field strength and potential in electrode system for creation a pulsed barrier discharge in atmospheric air in the presence of water in it in a droplet-film state. The calculations were performed under the conditions that the duration of the pulse front is ≈ 40 ns, the width of the gas gap is 3.2 mm, the thickness of the water films on its walls is 0.15 mm and the diameter of the droplets is 0.5 - 1.5 mm. It is shown that the presence of water droplets dramatically changes the distribution of the field in the gap: from uniform it becomes sharply inhomogeneous. The maximum field strength is observed at points on the surface of the drop, which are located nearest to the walls of the gap. This field strength is ≈ 2.5 times higher than that characteristic of a uniform field in the absence of a drop. The effect of neighboring drops on the distribution of the electric field is also considered. It

becomes significant (> 10%) when the distance between adjacent drops becomes less than 1.5 mm. References 8, figures 6.

Key words: pulsed barrier discharge, electric field strength, drop, water film, air.

Received: 02.01.2020

Accepted: 28.01.2020

Published: 26.02.2020

References

1. Vanraes P., Nikiforov A.Y., Leys Ch. Electrical Discharge in Water Treatment Technology for Micropollutant Decomposition. Chapter 15. InTech, 2016. Pp. 457-506. DOI: <http://dx.doi.org/10.5772/61830>
2. Bo Jiang, Jingtang Zheng, Shi Qiu, Qinhui Zhang, Zifeng Yan, Qingzhong Xue. Review on electrical discharge plasma technology for wastewater. *Chemical Engineering Journal*. 2014. No 236. Pp. 348-363. DOI: <https://doi.org/10.1016/j.cej.2013.09.090>
3. Shen Zhao, Chunjing Hao, Di Xu, Yiyong Wen, Jian Qiu, Kefu Liu. Effect of Electrical Parameters on Energy Field of Organic Pollutant Degradation in a Dielectric Barrier Discharge Reactor. *IEEE Transactions on Plasma Science*. 2017. Vol. 45. Issue 6. Pp. 1043-1050. DOI: <https://doi.org/10.1109/TPS.2017.2691726>
4. Dojchinovich B.P., Roglich G.M., Obradovich B.M., Kuraica M.M., Kostich M.M., Nesich J., Manojlovich D.D. Decolorization of Reactive Textile Dyes Using Water Falling Film Dielectric Barrier Discharge. *Journal of Hazardous Materials*. 2011. No 192. Pp. 763-771. DOI: <https://doi.org/10.1016/j.jhazmat.2011.05.086>
5. Bozhko I.V., Karlov O.M., Kondratenko I.P., Cherny D.V. Development of a Complex for the Treatment of Water by Impulse Barrier. *Tekhnichna Electrodynamika*. 2017. No 6. Pp. 80-86. DOI: <https://doi.org/10.15407/techned2017.06.080>
(Ukr)
6. Yavorovsky N.A., Kornev Ya.I., Preiss S.V., Peltzman S.S., Haskelberg M.B., Chen B.N. Active oxidizing particles in the water-air stream. *News of the Tomsk Polytechnic Institute*. 2006. Vol. 309. No 2. P.108-113. (Rus)
7. Schoenbach K.H., Joshi R.P., Stark R.H., Dobbs F.C., Beebe S.J. Bacterial Decontamination of Liquids with Pulsed Electric Fields. *IEEE Transactions on Dielectrics and Electrical Insulation*.

2000. Vol. 7. No 5. Pp. 637-645.

DOI:

<https://doi.org/10.1109/94.879359>

8. Kornev Ya.I., Isaev Yu.N., Ushakov V.Ya., Khaskelberg M.B., Yavorovskii N.A., Kolchanova V.A. Influence of the Distribution of Electric Fields in a Reactor of Electrodischarge Water Treatment on the Treatment Efficiency. *Russian Physics Journal*. 2004. Vol. 47. No 10. Pp. 1062-1070.

DOI: <https://doi.org/10.1007/s11182-005-0022-4>

[g/10.1007/s11182-005-0022-4](https://doi.org/10.1007/s11182-005-0022-4)

[PDF](#)



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)