

DOI: <https://doi.org/10.15407/techned2016.02.078>

ELECTROMAGNETIC ACOUSTIC TRANSDUCER FOR ULTRASONIC THICKNESS GAUGING OF FERROMAGNETIC METAL ITEMS WITHOUT REMOVING DIELECTRIC COATING

Journal	Tekhnichna elektrodynamika
Publisher	Institute of Electrodynamics National Academy of Science of Ukraine
ISSN	1607-7970 (print), 2218-1903 (online)
Issue	№ 2, 2016 (March/April)
Pages	78 – 82

Authors

R.P. Migushchenko¹, G.M. Suchkov¹, Kh.K. Radev², O.M. Petrishchev³, O.V. Desyatnichenko

1

¹ – National Technical University ‘Kharkiv Polytechnic Institute’,
21, Frunze str., Kharkiv, 61002, Ukraine,
e-mail: suchkov_gm@mail.ru

² – Technical University of Sofia,
1000, 8 Kl. Ohridski Blvd, Sofia, 1797, Bulgaria

³ – National Technical University of Ukraine ‘Kyiv Polytechnic Institute’,
37, Prospect Peremohy, Kyiv, 03056, Ukraine

A combined high-performance electromagnetic acoustic gauge for transforming electrical power into acoustic power and vice versa has been developed. It is designed to excite and accept ultrasonic high-frequency pulses in metallic items by using magnetic and electromagnetic fields in the presence of dielectric coatings with thickness up to 10 mm. Without changing the design this transducer can be used for checking items with flat or curved surfaces. At this only thickness of metal is measured. The new transducer allows significantly reduce cost of ultrasonic check by means of excluding operations for removal of protecting coating and its further renewal. The solution can be used for diagnostic operations in field of power engineering, metallurgy, transportation and other areas in which metal items with/without coatings are used. References 7, figures 5.

Key words: ultrasonic diagnosis, electromagnetic acoustic transducer, dielectric coating, thickness gauging.

Received: 15.12.2015

Accepted: 04.02.2016

Published: 18.03.2016

References

1. Vasenev Yu.G., Stupachenko S.G. Methods improve the monitoring gas and oil pipelines using the technical capabilities of defectoscopes SONATEST. *Kontrol. Diagnostika*. 2009. No 5. P. 50–54. (Rus)
2. Ermolov I.N., Lange Ju.V. Nondestructive testing. Vol. 3. Moskva: Mashinostroenie, 2004. 864 p. (Rus)
3. Izymov N.M., Linde D.P. Fundamentals of radio engineering. Moskva: Radio i sviaz. 1983. 376 p. (Rus)
4. Sudakova K.V., Kazjukevich I.L. On increasing the effectiveness of the quality control of steel products. *V mire nerazrushaiushchego kontrolya*. 2004. Vol. 3. P. 8–10. (Rus)
5. Suchkov G.M., Petrishchev O.N., Homyak Yu.V. Theory and practice of electromagnetic-acoustic control. Part 3. Kharkiv: Shchedra sadyba plus, 2015. 124 p. (Rus)
6. Maeda M., Hirasawa H., Yoshikawa T. The effects of film thickness on the reflection echo height of ultrasonic testing. *J. Jap. Soc. Nondestructive Inspection*. 2012. Vol. 61. No 9. P. 480–487.
7. Suchkov G.M., Petrishchev O.N., Cherednichenko I.V., Fedorov V.V., Desyatnichenko A.V., Khashchina S.V., Maslova M.S. Generator of Probing Pulses for EMA Flaw Detectors. *Russian Journal of Nondestructive Testing*

. 2012. Vol. 48. No 9. P. 537–540. DOI:
<https://doi.org/10.1134/S1061830912090082>

[PDF](#)