1994, □ 2
CONTENTS
Electrodynamics of electrical power devices
Tchemeris V.T. Influence of fast-varying magnetic field on electrical conducting particles
motion in gas-dust medium 3

Electric energy parameters conversion
Pyvnyak G.G., Vypanasenko S.L, Kovalev A.P. New principles of frequency converter
control in contact-free transport system8
Lipkovsky K.A., Modzarovsky A.G., Khalikov V.A. Comparative analysis of the
elemental transformer switching final-control structures11
Puzakov A.V., Baranov A.M. Widely regulating DC-to-DC converters design on two-section basis16
Senko V.I., Kalinichenko A.P., Lebedenko S.A., Fan Kuok-Zoong, Font Kuang Ving.
New algorithms of three-level PWM and their combined application for 3-phase inverters with
neutral

Ovcharenko AA., Yurchenko O.N., Skidanov V.M., Pavlov V.B., Rychkov V. A.

Analysis of pulse transis- tor converter operation 42

**Electromechanical energy conversion** 

Styazhkin V.P., Isakov V.N. Parametric forming	of mechanical characteristics of asynchronous
motor with phase-wound rotor	46
Asanbayev V.N., Babyak A. A., Saratov VA., S	Strikharchuk D.K. Improvement in the
effectiveness of heat power stations at industrial	plants 51
Lutskiv M.M., Kylany S. Pulse tracking drive for 54	combining of technological operations
Electric energy systems and installations	
Danko A.V., Mostovyak I.V, Novikova O.I. App	lication of method of zero, positive and nega
tive sequences symmetric systems	58

Varetzky Yu.0., Ravlik O.M., Bakhor Z.M. Features of simulating the processes at faults
to ground in 6-35 V circuits with insulated neutral 61
Nedzelsky I.S. Comparison of power grid models constructed on the basis of overlapping classic principle and overlapping principle when fictitious emf is brought in power grid passive circuit units64
Electrical and magnetic measurements
Popov V.Yu. Influence of potential electrodes thickness on four-electrode jig metric mesh
cons- tant
Brief reports

1	a	a	4	Г	2
	-	ы	-		_

Shadlovsky I.A., Zrazhevsky Yu.M. Leakage currents of electric transport pow	er circuit
with inductive energy transmission_	_71
Petrushin V.S., Wilbert Laurence. Asynchronous motor characteristics in a sys	stem consists
of thyristor converter electric drive and asynchronous motor with a feedback by r speed74	otational
Scientific and technical information	
"ELETTRICJTA SICURA". 1st Exhibition of safe electric material	